

IN THE CLAIMS

Please amend the claims as follows:

1-21. (Cancelled)

102 22. (Currently Amended) A method of reducing a voltage, comprising:

applying the voltage to a transistor;

~~reducing the voltage by a threshold voltage of the transistor; and~~

providing an output voltage at an output of the transistor, the output voltage equal

to the applied voltage reduced by the a threshold voltage of the transistor at an output of the
~~transistor~~, wherein the output of the transistor is coupled to a well that bounds the transistor.

102 23. (Previously Presented) The method of claim 22, wherein applying the voltage to the transistor comprises coupling the voltage to a first source/drain and a gate of the transistor.

⊖ 24. (Previously Presented) The method of claim 23, further comprising coupling the output of the transistor to a second source/drain of the transistor and to a semiconductor region in which the first and second source/drains are formed.

⊖ 25. (Previously Presented) The method of claim 24, wherein the first and second source/drains and the well are formed from a first type semiconductor material and the semiconductor region is formed from a second type semiconductor material.

⊖ 26. (Previously Presented) The method of claim 25, wherein the first and second source/drains contain a different dopant concentration relative to the well.

102 27. (Currently Amended) A method of reducing a voltage, comprising:

applying the voltage to a first source/drain and a gate of a transistor;

~~reducing the voltage by a threshold voltage of the transistor; and~~

102 providing an output voltage at a second source/drain of the transistor and a well
102 bounding the transistor, the output voltage equal to the applied voltage reduced by the a
threshold voltage of the transistor ~~at a second source/drain of the transistor and a well bounding~~
~~the transistor.~~

102 28. (Previously Presented) The method of claim 27, further comprising coupling the well that
bounds the transistor to the second source/drain of the transistor.

⊖ 29. (Previously Presented) The method of claim 28, further comprising coupling a
semiconductor region in which the first and second source/drains are formed to the well region
and to the second source/drain.

102 ③0. (Previously Presented) A method of reducing a voltage applied to a circuit, comprising:
coupling a transistor between the voltage and the circuit to reduce the voltage by a
threshold voltage of the transistor; and
coupling a well, that isolates the transistor from a substrate, to the circuit.

102 31. (Previously Presented) The method of claim 30, wherein coupling the transistor between
the voltage and the circuit comprises:

coupling one source/drain of the transistor to the voltage;
coupling a gate of the transistor to the voltage; and
coupling another source/drain of the transistor to the circuit.

102 32. (Previously Presented) The method of claim 30, wherein coupling the transistor between
the voltage and the circuit comprises:

coupling one source/drain of the transistor to the voltage;
coupling a gate of the transistor to the voltage;
coupling another source/drain of the transistor to the circuit; and
coupling a semiconductor region, containing the one source/drain and the other
source/drain, to the circuit.

well

102 33. (Previously Presented) The method of claim 32, wherein the one source/drain, the other source/drain and the well are formed from a first type semiconductor material and the semiconductor region containing the one source/drain and the other source/drain is formed from a second type semiconductor material.

102
can read "region" as
a well, since no
well is described

34. (Currently Amended) A method of reducing a voltage, comprising:
applying the voltage to a first source/drain and a gate of a transistor;
~~reducing the voltage by a threshold voltage of the transistor;~~ and
providing an output voltage at a second source/drain of the transistor, the output
voltage equal to the applied voltage reduced by the threshold voltage of the transistor at a second
source/drain of the transistor, wherein a semiconductor region containing the first and second
source/drains is coupled to the second source/drain of the transistor.

reconnect both
well + region

35. (Previously Presented) The method of claim 34, further comprising:
isolating the transistor from a substrate by a well formed between the region
containing the first and second source/drains and the substrate; and
coupling the well to the second source/drain and to the semiconductor region
containing both source/drains.

36. (Previously Presented) The method of claim 35, wherein the first and second
source/drains and the well are a first type semiconductor material and the region containing the
source/drains is a second type semiconductor material.

37. (Previously Presented) The method of claim 36, wherein the first and second
source/drains have a different dopant concentration than the well.

38. (Currently Amended) A method of reducing voltage from an external voltage supply in
an integrated circuit, comprising:

coupling a transistor of the integrated circuit between the external supply voltage and an internal circuit of the integrated circuit;

~~reducing the external supply voltage applied~~ applying a voltage at the transistor output to the internal circuit, the applied voltage reduced from the external supply voltage by a threshold voltage of the transistor;

isolating the transistor from a substrate region of the integrated circuit by a well formed in the substrate region; and

coupling the well to the internal circuit.

39. (Previously Presented) The method of claim 38, wherein coupling the transistor between the external supply voltage and the internal circuit, comprises:

coupling a first source/drain and a gate of the transistor to the external supply voltage; and

coupling a second source/drain of the transistor, the well, and a semiconductor region containing the first and second source/drains of the transistor to the internal circuit.

40. (Previously Presented) The method of claim 38, wherein the integrated circuit is a memory device and the internal circuit is a memory cell of the memory device.

(41) (Currently Amended) A method of reducing voltage, comprising:

applying the voltage to a first transistor, wherein a second transistor is coupled to the first transistor;

~~reducing the voltage;~~ and

providing an output the reduced voltage at an output of the second transistor, the output voltage equal to the applied voltage reduced by a threshold voltage of the first transistor and a threshold voltage of a second transistor, and wherein a well, bounding the first transistor and the second transistor, is coupled to the output.

(not shown)

42. (Previously Presented) The method of claim 41, wherein applying the voltage to the first transistor comprises applying the voltage to a first source/drain and a gate of the first transistor.

43. (Previously Presented) The method of claim 42, wherein a second source/drain of the first transistor and a first source/drain of the second transistor are integrally formed and are coupled to a gate of the second transistor.

44. (Previously Presented) The method of claim 43, wherein a second source/drain of the second transistor is coupled to the well and to a semiconductor region containing the source/drains of the first and second transistors.

45. (Currently Amended) A method of reducing voltage, comprising:
applying the voltage to a first transistor, wherein the first transistor is coupled to a second transistor;
reducing the voltage; and
providing an output the reduced voltage at an output of the second transistor, the output voltage equal to the applied voltage reduced by a threshold voltage of both the first transistor and the second transistor, and wherein a first well, bounding the first transistor, is coupled to the second transistor and a second well, bounding the second transistor, is coupled to the output.

46. (Previously Presented) The method of claim 45, wherein applying the voltage to the first transistor comprises applying the voltage to a first source/drain and a gate of the first transistor.

47. (Previously Presented) The method of claim 46, wherein a second source/drain of the first transistor is coupled to a first source/drain and a gate of the second transistor and a second source/drain of the second transistor is coupled to the output.

48. (Previously Presented) The method of claim 47, wherein the well of the first transistor is coupled to the second source/drain of the first transistor and to the first source/drain of the second transistor, and the well of the second transistor is coupled to the second source/drain of the second transistor and to the output.

102
FIG 8
col. 15

49. (Currently Amended) A method of reducing a voltage, comprising:

applying the voltage to a first source/drain and a gate of a first transistor, wherein a second source/drain of the first transistor is integrally formed with a first source/drain of a second transistor to form a common source/drain and the common source/drain is coupled to a gate of the second transistor;

~~reducing the voltage;~~ and

providing an output ~~the reduced~~ voltage at a second source/drain of the second transistor, wherein the output voltage is reduced from the applied voltage by a threshold voltage of both the first transistor and the second transistor.

102

50. (Previously Presented) The method of claim 49, wherein a semiconductor region containing the first and second source/drains and common source/drain of the first and second transistors is coupled to the second source/drain of the second transistor.

51. (Previously Presented) The method of claim 50, wherein a well bounding the first transistor and the second transistor is coupled to the second source/drain of the second transistor.

52. (Currently Amended) A method of reducing voltage, comprising:

applying the voltage to a first source/drain and a gate of a first transistor, wherein a second source/drain of the first transistor is coupled to a first source/drain and a gate of a second transistor; *(not shown)*

~~reducing the voltage;~~ and

providing an output ~~the reduced~~ voltage at a second source/drain of the second transistor, wherein the output voltage is reduced from the applied voltage by a threshold voltage of both the first transistor and the second transistor.

53. (Previously Presented) The method of claim 52, wherein a first semiconductor region containing the first and second source/drains of the first transistor is coupled to the second source/drain of the first transistor and wherein a second semiconductor region containing the first and second source/drains of the second transistor is coupled to the second source/drain of the second transistor.

54. (Previously Presented) The method of claim 53, wherein a first well bounding the first transistor is coupled to the second source/drain of the first transistor and wherein a second well bounding the second transistor is coupled to the second source/drain of the second transistor.

102
FIG. 8
col. 15

55. (Previously Presented) A method of regulating a voltage, comprising:
applying the voltage to a voltage reduction circuit; and
applying a signal to a switching circuit coupled to the voltage reduction circuit to cause the voltage reduction circuit to be activated to reduce the voltage by a predetermined amount; and

wherein applying the voltage to the voltage reduction circuit comprises applying the voltage to a first source/drain of a transistor and wherein:

a gate of the transistor is coupled to the switching circuit;
a second source/drain of the transistor is coupled to a node; and
a semiconductor region of the transistor containing the first and second source/drains is coupled to the node.

56. (Canceled)

102

57. (Previously Presented) The method of claim 55, further comprising applying the voltage to a second voltage reduction circuit that is coupled to the switching circuit.

58. (Previously Presented) The method of claim 57, wherein applying the voltage to the second voltage reduction circuit comprises applying the voltage to a first source/drain and a gate

of a transistor and wherein a second source/drain of the transistor is coupled to the switching circuit.

59. (Previously Presented) The method of claim 57, wherein applying the voltage to the second voltage reduction circuit comprises applying the voltage to a first source/drain and a gate of a first transistor, and wherein:

a second source/drain of the first transistor is coupled to a first source/drain and to a gate of a second transistor;

a first well, isolating the first transistor from a substrate, is coupled to the first source/drain of the second transistor;

a second source/drain of the second transistor is coupled to the switching circuit; and

a second well, isolating the second transistor from the substrate, is coupled to the switching circuit.

60. (Previously Presented) The method of claim 57, wherein coupling another voltage reduction circuit to the switching circuit comprises:

applying the voltage to a first source/drain and a gate of a first transistor, wherein a second source/drain of the first transistor is integrally formed with a first source/drain of a second transistor to form a common source/drain and the common source/drain is coupled to a gate of the second transistor; and

providing a reduced voltage at a second source/drain of the second transistor coupled to the switching circuit, wherein the voltage is reduced by a threshold voltage of both the first transistor and the second transistor.

6. (Currently Amended) A method of regulating a voltage, comprising:

applying the voltage to a first source/drain of a transistor;

biasing a well of the transistor to a second source/drain;

~~reducing the voltage~~; and

102
FB.7

providing an output the reduced voltage equal to the applied voltage reduced by a threshold voltage of the transistor at the second source/drain of the transistor in response to a gate signal applied to a gate of the transistor to activate the transistor.

102 62. (Previously Presented) The method of claim 61, further comprising applying the gate signal to the gate of the transistor in response to an enable signal being applied to a switching circuit coupled to the gate.

63. (Previously Presented) The method of claim 62, wherein applying the gate signal to the gate of the transistor comprises:

generating the gate signal by applying the reduced voltage to the switching circuit; and

applying the enable signal to the switching circuit to apply the gate signal to the gate of the transistor.

64. (Previously Presented) The method of claim 63, wherein generating the gate signal comprises applying the reduced voltage to a voltage divider circuit.

65 (Currently Amended) A method of operating an integrated circuit, comprising:
applying an external voltage to an input of the integrated circuit;
generating a reduced voltage from the external voltage to operate at least one internal circuit of the integrated circuit, wherein generating the reduced voltage includes:

applying the external voltage to a transistor;

~~reducing the voltage external voltage by a threshold voltage of the transistor;~~ and

providing an output the reduced voltage at an output of the transistor, the output voltage equal to the applied voltage reduced by a threshold of the transistor,

wherein the output of the transistor is coupled to a well that isolates the transistor from a substrate of the integrated circuit; and

applying the reduced voltage to the at least one internal circuit.

66. (Previously Presented) The method of claim 65, wherein applying the voltage to the transistor comprises coupling the external voltage to a first source/drain and a gate of the transistor.

67. (Previously Presented) The method of claim 66, wherein applying the reduced voltage to the at least one internal circuit comprises coupling a second source/drain of the transistor and a semiconductor region containing the first and second source/drains to the at least one internal circuit.

68. (Previously Presented) The method of claim 65, wherein the integrated circuit is a memory device and the at least one internal circuit is a memory cell.

69. (Previously Presented) A method of operating an integrated circuit, comprising:

applying an external voltage to an input of the integrated circuit;

generating a reduced voltage from the external voltage to operate at least one internal circuit of the integrated circuit, wherein generating the reduced voltage includes:

applying the external voltage to a source/drain and a gate of a transistor;

reducing the external voltage by a threshold voltage of the transistor; and

providing the reduced voltage at a second source/drain of the transistor,

and

applying the reduced voltage to the at least one internal circuit, wherein a well that isolates the transistor from a substrate of the integrated circuit is coupled to the at least one internal circuit.

70. -71. (Cancelled)

72. (Currently Amended) A method of operating an integrated circuit, comprising:

applying an external voltage to an input of the integrated circuit;

generating a reduced voltage from the external voltage to operate at least one internal circuit of the integrated circuit, wherein generating the reduced voltage includes:

applying the voltage to a first source/drain and a gate of a first transistor, wherein a second source/drain of the first transistor is integrally formed with a first source/drain of a second transistor to form a common source/drain and the common source/drain is coupled to a gate of the second transistor;

~~reducing the external voltage by a threshold voltage of the transistor by a threshold voltage of both the first transistor and the second transistor; and~~

providing an output the reduced voltage at a second source/drain of the second transistor, the output voltage equal to the external voltage reduced by a threshold voltage of both the first transistor and the second transistor; and applying the reduced voltage to the at least one internal circuit, wherein a semiconductor region containing the first and second source/drains and common source/drain of the first and second transistors is coupled to the at least one internal circuit.

73.- 74. (Canceled)

(75) (Currently Amended) A method of operating an integrated circuit, comprising:

applying an external voltage to an input of the integrated circuit;

generating a reduced voltage from the external voltage to operate at least one internal circuit of the integrated circuit, wherein generating the reduced voltage includes:

applying the voltage to a first source/drain and a gate of a first transistor, wherein a second source/drain of the first transistor is coupled to a first source/drain and a gate of a second transistor;

~~reducing the external voltage by a threshold voltage of the transistor by a threshold voltage of both the first transistor and the second transistor; and~~

providing the reduced voltage at a second source/drain of the second transistor, the reduced voltage equal to the external voltage reduced by a threshold voltage of both the first transistor and the second transistor; and

applying the reduced voltage to the at least one internal circuit, wherein a first semiconductor region containing the first and second source/drains of the first transistor is coupled to the first source/drain and the gate of the second transistor and wherein a second semiconductor region containing the first and second source/drains of the second transistor is coupled to the at least one internal circuit.

76. – 77. (Cancelled)